

**TECHNICAL DOCUMENTATION O-RINGS - JIS Sizes G Series**

Size	ID		C/S (W)		ID		C/S (W)	
	mm	±	mm	in	±	in	±	
G-25	24.4	0.15	3.1	0.961	0.006	0.122	0.004	
G-30	29.4	0.15	3.1	1.157	0.006	0.122	0.004	
G-35	34.4	0.15	3.1	1.354	0.006	0.122	0.004	
G-40	39.4	0.15	3.1	1.551	0.006	0.122	0.004	
G-45	44.4	0.25	3.1	1.748	0.010	0.122	0.004	
G-50	49.4	0.25	3.1	1.945	0.010	0.122	0.004	
G-55	54.4	0.25	3.1	2.142	0.010	0.122	0.004	
G-60	59.4	0.25	3.1	2.339	0.010	0.122	0.004	
G-65	64.4	0.25	3.1	2.535	0.010	0.122	0.004	
G-70	69.4	0.25	3.1	2.732	0.010	0.122	0.004	
G-75	74.4	0.40	3.1	2.929	0.016	0.122	0.004	
G-80	79.4	0.40	3.1	3.126	0.016	0.122	0.004	
G-85	84.4	0.40	3.1	3.323	0.016	0.122	0.004	
G-90	89.4	0.40	3.1	3.520	0.016	0.122	0.004	
G-95	94.4	0.40	3.1	3.717	0.016	0.122	0.004	
G-100	99.4	0.40	3.1	3.913	0.016	0.122	0.004	
G-105	104.4	0.40	3.1	4.110	0.016	0.122	0.004	
G-110	109.4	0.40	3.1	4.307	0.016	0.122	0.004	
G-115	114.4	0.40	3.1	4.504	0.016	0.122	0.004	
G-120	119.4	0.40	3.1	4.701	0.016	0.122	0.004	
G-125	124.4	0.40	3.1	4.898	0.016	0.122	0.004	
G-130	129.4	0.60	3.1	5.094	0.024	0.122	0.004	
G-135	134.4	0.60	3.1	5.291	0.024	0.122	0.004	
G-140	139.4	0.60	3.1	5.488	0.024	0.122	0.004	
G-145	144.4	0.60	3.1	5.685	0.024	0.122	0.004	
G-150	149.3	0.60	5.7	5.878	0.024	0.224	0.006	
G-155	154.3	0.60	5.7	6.075	0.024	0.224	0.006	
G-160	159.3	0.60	5.7	6.272	0.024	0.224	0.006	
G-165	164.3	0.60	5.7	6.469	0.024	0.224	0.006	
G-170	169.3	0.60	5.7	6.665	0.024	0.224	0.006	
G-175	174.3	0.60	5.7	6.862	0.024	0.224	0.006	
G-180	179.3	0.60	5.7	7.059	0.024	0.224	0.006	
G-185	184.3	0.80	5.7	7.256	0.031	0.224	0.006	
G-190	189.3	0.80	5.7	7.453	0.031	0.224	0.006	
G-195	194.3	0.80	5.7	7.650	0.031	0.224	0.006	
G-200	199.3	0.80	5.7	7.846	0.031	0.224	0.006	
G-210	209.3	0.80	5.7	8.240	0.031	0.224	0.006	
G-220	219.3	0.80	5.7	8.634	0.031	0.224	0.006	
G-230	229.3	0.80	5.7	9.028	0.031	0.224	0.006	
G-240	239.3	0.80	5.7	9.421	0.031	0.224	0.006	
G-250	249.3	0.80	5.7	9.815	0.031	0.224	0.006	

G-255	254.3	0.80	5.7	10.012	0.031	0.224	0.006
G-260	259.3	0.80	5.7	10.209	0.031	0.224	0.006
G-270	269.3	0.80	5.7	10.602	0.031	0.224	0.006
G-280	279.3	0.80	5.7	10.996	0.031	0.224	0.006
G-290	289.3	0.80	5.7	11.390	0.031	0.224	0.006
G-300	299.3	0.80	5.7	11.783	0.031	0.224	0.006